

# Xerox® Phaser® 3330 Printer



System Specification	Phaser 3330
<b>One-Sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 42 ppm Up to 40 ppm Up to 34 ppm
<b>Two-Sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 21 ppm Up to 20 ppm Up to 17 ppm
<b>Monthly Duty Cycle<sup>1</sup></b>	Up to 80,000 pages / month
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>	Up to 6,000 pages
<b>Processor</b>	1 GHz
<b>Memory</b>	512 MB
<b>Connectivity</b>	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi
Paper Handling	
Bypass Tray	
<b>Capacity<sup>3</sup></b>	50 sheets
<b>Sizes</b>	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
<b>Weights</b>	16 lb. bond to 58 lb. cover / 60 to 220 gsm
<b>Media Types</b>	Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies
Tray 1	
<b>Capacity<sup>3</sup></b>	250 sheets
<b>Sizes</b>	Custom Sizes 3.9 x 5.8 in. to 8.5 x 14 in. / 99 x 147 mm to 216 x 356 mm
<b>Weights</b>	16 lb. bond to 43 lb. bond / 60 to 163 gsm
<b>Media Types</b>	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled
Additional Tray	
<b>Capacity<sup>3</sup></b>	550 sheets

# Xerox® Phaser® 3330 Printer

Additional Tray	
<b>Sizes</b>	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
<b>Weights</b>	16 lb. to 43 lb. bond / 60 to 163 gsm
<b>Media Types</b>	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled
Total Capacity	
<b>Device Standard Capacity<sup>3</sup></b>	300 sheets
<b>Device Total Capacity<sup>3</sup></b>	850 sheets
Paper Output	
<b>Output Capacity<sup>3</sup></b>	150 sheets
<b>Automatic 2-Sided</b>	Standard
Device Specification	
Electrical Requirements	
<b>North America</b>	110-127 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 7A
<b>Europe</b>	220-240 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 5A
Power Consumption	
<b>Operation<sup>4</sup></b>	Maximum 700 watts
<b>Standby Mode<sup>4</sup></b>	Maximum 50 watts
<b>Power Off Mode<sup>4</sup></b>	Maximum 0.1 watts
<b>Sleep Mode<sup>4</sup></b>	Maximum 3.5 watts
<b>Warm-up (from Sleep Mode)</b>	As fast as 35 seconds
Operating Environment	
<b>Required Temperature Range</b>	
Storage	32°F to 104°F / 0°C to 40°C
Operating	50°F to 90°F / 10°C to 32°C
<b>Required Relative Humidity</b>	20% to 80%
<b>Sound Power Levels</b>	
Operating	54 dB(A) or less
Standby	26 dB(A) or less
<b>Sound Pressure Levels</b>	
Operating	54 dB(A) or less
Standby	26 dB(A) or less
Dimensions and Weight (unpacked)	
<b>Phaser 3330</b>	Width: 14.4 in. / 366 mm Depth: 14.4 in. / 366 mm Height: 11.4 in. / 289.6 mm Weight: 23.37 lb. / 10.6 kg
<b>550-sheet Paper Tray</b>	Width: 14.4 in. / 366 mm Depth: 17.9 in. / 454 mm Height: 5.7 in. / 146 mm Weight: 11.82 lb. / 5.36 kg
Dimensions and Weight (packaged)	
<b>Phaser 3330</b>	Width: 17.7 in. / 449.6 mm Depth: 17.7 in. / 449.6 mm Height: 15.9 in. / 403.9 mm Weight: 28.31 lb. / 12.84 kg

# Xerox® Phaser® 3330 Printer

Dimensions and Weight (packaged)	
<b>550-sheet Paper Tray</b>	Width: 22.2 in. / 563 mm Depth: 19.6 in. / 497 mm Height: 11.2 in. / 285 mm Weight: 16.8 lb. / 7.62 kg
System Certification/Regulatory Compliance	
<b>Certifications</b>	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition Section 508 NOM GS Mark EAC RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix™ Certified Cerner (undergoing evaluation) Apple® AirPrint® 1.5 certification Google Cloud Print™ (device is compliant/tested, but has not been formerly certified) Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .
Print	
<b>First-Page-Out Time</b>	As fast as 6.5 seconds <sup>5</sup>
<b>Resolution</b>	Up to 1200 x 1200 dpi image quality
<b>Page Description Languages</b>	PostScript 3 compatible PCL® 5e, 6 PDF Direct TIFF JPEG
<b>Maximum Print Area</b>	4 mm edge of paper
<b>Print Features</b>	Watermarks Collation Automatic Two-sided Printing N-up Poster Printing Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save Save and Print
<b>Print from USB</b>	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL
<b>Operating Systems</b>	Microsoft® Windows® Vista and later Mac OS® 10.8.x and later Various Linux® and Unix distributions

# Xerox® Phaser® 3330 Printer

Print					
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®, EtherTalk® Microsoft Windows Networking over IP Bonjour® / Airprint® IPv6 Secure FTP Most protocols not in use can be disabled				
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP				
<b>Font Capability</b>	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font				
Mobile Solutions and Mobile Device Apps					
<b>Xerox® Mobile Express Driver®</b>	Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.				
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.				
<b>Apple® AirPrint®</b>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.				
<b>Google Cloud Print™</b>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.*				
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.				
Security					
<b>Security Features</b>	802.1x Secure HTTPS (SSL/TLS) Secure IPP Secure Print SSL IP Filtering IPv6 SNMP v3 IPsec WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise				
WiFi Security					
	<table border="1"> <thead> <tr> <th>Authentication Method</th> <th>Encryption</th> </tr> </thead> <tbody> <tr> <td>Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2™ Enterprise  WPA Enterprise Authentication Method options: • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TTLS PAP • EAP-TTLS CHAP</td> <td>WEP 64 / 128-bit ASCII / HEX TKIP AES TKIP AES</td> </tr> </tbody> </table>	Authentication Method	Encryption	Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2™ Enterprise  WPA Enterprise Authentication Method options: • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TTLS PAP • EAP-TTLS CHAP	WEP 64 / 128-bit ASCII / HEX TKIP AES TKIP AES
Authentication Method	Encryption				
Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2™ Enterprise  WPA Enterprise Authentication Method options: • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TTLS PAP • EAP-TTLS CHAP	WEP 64 / 128-bit ASCII / HEX TKIP AES TKIP AES				
Device Management					
Xerox® CentreWare® Web					
<b>Device Status</b>	Web server embedded • Tray status/contents • Consumables status				
<b>Print Queue Viewing</b>	Complete job print queue management—hold, release, promote and delete				

# Xerox® Phaser® 3330 Printer

Device Management		
<b>Xerox® CentreWare® Web</b>		
<b>Job Submission</b>	Print-ready files (PS, PCL®5c/6, PDF, TIFF) Output feature selection	
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device.	
<b>Browsers</b>	Microsoft® Internet Explorer 6, 7 Firefox® 2., 3 Safari® 3.0	
<b>Xerox® CentreWare® Internet Services – Integrated Device Web Page</b>		
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> </ul>	
<b>Xerox® Standard Accounting (Standard)</b>		
<b>Tracking</b>	Print usage	
<b>Accounting</b>	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)	
<b>Features</b>	<ul style="list-style-type: none"> <li>• Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>• Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>	
<b>Remote Print Services</b>		
<b>Xerox® MeterAssistant® Service</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
<b>Xerox® SuppliesAssistant® Service</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
<b>Maintenance Assistant</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.	
<b>What's In The Box</b>		
	<ul style="list-style-type: none"> <li>• Phaser 3330 Printer</li> <li>• Standard Capacity Print cartridge: 2,600 pages<sup>7</sup></li> <li>• Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement</li> <li>• Installation Guide</li> <li>• Quick Use Guides</li> <li>• Power cord</li> </ul>	
<b>Supplies and Accessories</b>	<b>Quantity</b>	<b>Part Number</b>
<b>Supplies</b>		
<b>Extra-High Capacity Print Cartridges</b>	15,000 standard pages <sup>7</sup>	106R03624
<b>High Capacity Print Cartridges</b>	8,500 standard pages <sup>7</sup>	106R03622
<b>Standard Capacity Print Cartridges</b>	2,600 standard pages <sup>7</sup>	106R03620
<b>Drum Cartridge</b>	30,000 standard pages <sup>8</sup>	101R00555
<b>Accessories</b>		
<b>550-sheet Paper Tray</b>	097N02254	
<b>Near Field Communication (NFC) Enablement Kit</b>	097N02255	
<b>Card Reader Enablement Kit (with Card Reader)</b>	497K18000	
<b>Card Reader Enablement Kit (without Card Reader)</b>	497K18010	

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Printing from USB.

<sup>6</sup> Depending on the specific mobile device, versions or vendor, the mobile device may require a free download of the app from the appropriate store(s).

<sup>7</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>8</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

# Xerox® Phaser® 3330 Printer

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.  
For more information, visit [www.xerox.com/about-xerox/recycling](http://www.xerox.com/about-xerox/recycling).

©2017 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, SuppliesAssistant®, and Phaser® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice.  
10/17 BR19338 333SS-01UC

